



No. 25T04Z100360-046

2 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Luxshare Precision Limited 5G Mobile Phone T Phone 3 Pro are as follows:

Table 2.1: Highest Reported SAR (10g)

Mode	Antenna	Highest Reported SAR (10g)		
		10g SAR Head	10g SAR Body	10g SAR Limb
GSM 900	0	0.19	0.48	1.07
GSM 900	2	0.25	0.48	1.22
GSM 1800	1	0.04	0.76	1.90
GSM 1800	4	0.54	0.54	1.83
WCDMA Band1	1	0.05	0.85	1.98
WCDMA Band1	4	0.64	1.10	1.73
WCDMA Band8	0	0.33	0.59	1.62
WCDMA Band8	2	0.42	0.61	1.26
LTE Band 1	1	0.08	0.89	2.35
LTE Band 1	4	0.48	0.93	2.09
LTE Band 3	1	0.09	1.03	2.51
LTE Band 3	4	0.54	0.79	2.40
LTE Band 7	1	0.03	0.57	2.30
LTE Band 7	4	0.44	0.73	1.70
LTE Band 8	0	0.31	0.89	1.82
LTE Band 8	2	0.50	0.66	1.14
LTE Band 20	0	0.19	0.72	1.76
LTE Band 20	2	0.45	0.68	0.91
LTE Band 28	0	0.15	0.51	1.78
LTE Band 28	2	0.30	0.58	0.66
LTE Band 38 PC3	1	0.05	0.59	2.99
LTE Band 38 PC2	1	0.08	0.60	2.99
LTE Band 38 PC3	4	0.72	0.48	1.90
LTE Band 38 PC2	4	0.72	0.59	2.16
LTE Band 40	1	0.05	0.72	2.64
n1	1	0.10	1.18	2.98
n1	4	0.63	1.40	2.70
n3	1	0.19	1.21	2.56
n3	4	0.79	0.83	2.72
n7	1	0.05	0.88	2.77
n7	4	0.79	0.95	2.09
n28	0	0.16	0.55	1.50
n28	2	0.20	0.48	0.62
n41(n38)	1	0.11	0.80	2.79
n41(n38)	4	0.94	0.86	2.42
n41(n38)	3	0.44	1.06	2.83
n41(n38)	8	0.89	0.75	2.44
n77(n78)	5	0.58	0.68	1.01



No. 25T04Z100360-046

n77(n78)	7	0.77	0.83	2.74
n77(n78)	4	0.52	0.96	2.50
n77(n78)	2	0.29	0.47	1.42
WIFI 2.4G	6	0.49	0.54	1.56
WIFI 2.4G	9	0.22	0.48	1.17
WIFI 5G	7	0.55	0.77	1.06
WIFI 5G	9	0.27	0.56	1.74
WIFI 6E	7	0.62	0.43	1.33
WIFI 6E	9	0.52	0.43	1.69
BT	7	0.11	0.09	0.26

Note1: This device supports both (5G NR n38/n78) and (5G NR n41/n77). Since the supported frequency span for (5G NR n38/n78) falls completely within the supports frequency span for (5G NR n41/n77), both bands have the same target power, and both bands share the same transmission path; therefore, SAR was only assessed for (5G NR n41/n77).

The SAR values found for the Mobile Phone are below the maximum recommended levels of 2.0 W/Kg (4.0 W/Kg for limb SAR) as averaged over any 10g tissue according to the EN 50360:2017+EN 50566:2017.

The measurement together with the test system set-up is described in chapter 8 of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The maximum SAR value is obtained at the case of **(Table 2.1)**, and the values are:

Head: 0.94 W/kg (10g)

Body: 1.40 W/kg (10g)

Limb: 2.99 W/kg (10g)