



No. 25T04Z100362-028

2 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Luxshare Precision Limited 5G Mobile Phone T Phone 3 are as follows:

Table 2.1: Highest Reported SAR (10g)

Mode	Antenna	Highest Reported SAR (10g)		
		10g SAR Head	10g SAR Body	10g SAR Limbs
GSM 900	0	0.20	0.64	0.84
GSM 900	3	0.58	0.45	1.40
GSM 1800	1	0.10	0.34	1.12
GSM 1800	3	0.44	0.55	1.43
WCDMA Band I	1	0.39	0.95	2.52
WCDMA Band I	3	0.64	0.91	2.26
WCDMA Band VIII	0	0.20	0.89	1.28
WCDMA Band VIII	3	0.20	0.20	0.78
LTE Band 1	1	0.28	1.02	2.86
LTE Band 1	3	0.88	1.35	2.01
LTE Band 3	1	0.23	0.80	2.67
LTE Band 3	3	0.86	1.18	2.35
LTE Band 7	3	0.48	0.74	2.10
LTE Band 7	1	0.26	0.72	1.37
LTE Band 8	0	0.22	0.78	1.09
LTE Band 8	3	0.61	0.66	1.31
LTE Band 20	0	0.24	0.61	0.91
LTE Band 20	3	0.58	0.43	0.99
LTE Band 28	0	0.23	0.54	0.99
LTE Band 28	3	0.48	0.43	1.13
LTE Band 38 PC3	3	0.15	0.74	1.99
LTE Band 38 PC3	1	0.07	0.50	1.16
LTE Band 38 PC2	3	0.10	0.50	1.58
LTE Band 38 PC2	1	0.06	0.42	1.00
N1	1	0.28	0.77	1.87
N1	3	0.56	1.13	2.22
N3	1	0.14	0.71	2.47
N3	3	0.86	1.02	2.20
N7	3	0.56	1.29	2.56
N7	1	0.13	0.60	1.30
N28	0	0.21	0.26	0.49
N28	3	0.36	0.18	0.60
N38 PC2	3	0.54	0.89	2.25
N38 PC2	1	0.13	0.48	1.13
N78	4	0.43	0.57	2.85
N78	2	0.02	0.92	1.28
N78	0	<0.01	0.15	0.26
N78	6	0.30	0.30	0.77
WLAN 2.4 GHz	5	0.46	0.42	0.96



No. 25T04Z100362-028

WLAN 5 GHz	5	0.26	0.45	1.02
BT	5	0.04	0.04	0.12

The SAR values found for the Mobile Phone are below the maximum recommended levels of 2.0 W/Kg as averaged over any 10g tissue according to the EN 50360:2017/ EN 50566:2017.

The measurement together with the test system set-up is described in chapter 8 of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The maximum SAR value is obtained at the case of (Table 2.1), and the values are:

Head: 0.88 W/kg (10g)

Body: 1.35 W/kg (10g)

Limb: 2.86 W/kg (10g)